



Type	Profile				Description	Manual App Control	
	Fixture ID	Model / Name	Icon	Fixture mode			
0-10V	19776**	CBU-SENS-HB PS-LS-T-010Lin		PWM/1ch/Dim{OHI,HWTemp,Presence,Daylight}	Presence & Light Sensor, 0-10V controller with linear dimming curve.	Dimmer: 0-10V	 It also appears under the "Sensors" Tab.
	19780	CBU-SENS-HB PS-LS-T-010Log		PWM/1ch/Dim{OHI,HWTemp,Presence,Daylight}	Presence & Light Sensor, 0-10V controller with logarithmic dimming curve.	Dimmer: 0-10V	 It also appears under the "Sensors" Tab.
Misc.	19775	CBU-SENS-HB PS-LS		Sensor{OHI,HWTemp,Presence,Daylight}	Presence & Light Sensor	-	It appears under the "Sensors" Tab.
	19781	CBU-SENS-HB PS-LS-NoLED		Sensor{OHI,HWTemp,Presence,Daylight}	Presence & Light Sensor. Presence detection LED is inhibited (LED will only work for manual identification of sensors during the commissioning)	-	It appears under the "Sensors" Tab.

** Default profile

Additional Information

Summary of some terms and abbreviations that have been used throughout the document.

Abbreviation:	Description:
Lin	Linear dimming curve.
Log	Logarithmic dimming curve.
PS	Presence Sensor.
LS	Light Sensor.
NoLED	Fixture works with the presence detection LED inhibited.



Revision history

Date:	Version:	Description:
26/09/2023	1.0	Initial release.

