



YP-61+YC-12 Power Cord / IEC 320-C13 Connector

British

Specifications

- Part No. : YP-61+YC-12
- Standard : BS 1363(A)
- IEC 320-C13 Connector
- UK Plug : Type G
- Rating : 250VAC @ 3A/5A/10A/13A
- Fuse : 250VAC @ 13A
- Cord. : H05VVF, 0.75mm²x3G
- Color : Black
- Length : 6 feet
- Withstand : 2000VAC@15M
- Safety : ASTA, Singapore PSB, Saudi Arabia SASO, HK Safety mark
- Weight (lbs) : 0.1



Used in: UK, Ireland, Cyprus, Malta, Malaysia, Singapore, Hong Kong.

The Type G electrical plug has three rectangular blades in a triangular pattern and has an incorporated fuse (usually a 3 amps fuse for smaller appliances such as a computer and a 13 amps one for heavy duty appliances such as heaters). British sockets have shutters on the live and neutral contacts so that foreign objects can't be introduced into them.

YC-12 IEC 60320 C13 Connector



Country:	Wire Type:	Rating:
North-American continent 	SVT (3C) 18AWG SVT-shielded (3C) 18AWG SJT, SJT Shielded, 18AWG SJTW, SJTW Shielded, 18AWG SPT-2, 18AWG SJT, SJT-shielded, 16AWG SJTW, SJTW Shielded, 16AWG SJT, SJT-shielded, 14AWG SJTW, SJTW Shielded, 14AWG	10A,13A,15A 125V~,250V
	H05VV-F, 0.75mm ² x3C H05VV-F, 1.00mm ² x3C	10A 250V
Australia / New-Zealand 	H05VV-F, 0.75mm ² x3C H05VV-F, 1.00mm ² x3C	10A 250V
 Japan	(H)VCTF, 0.75mm ² (H)VCTF, 1.00mm ² (H)VCTF, 1.25mm ²	7A 125V 12A 125V 15A 125V
China 	RVV, 0.75mm ² RVV, 1.0mm ² RVV, 1.25mm ²	10A 250V
Taiwan 	(H)VCTF, 0.75mm ² (H)VCTF, 1.25mm ²	7A 125V 12A 125V 15A 125V
Korea 	(H)VCTF, 0.75mm ²	7A 250V